


STAINLESS STEEL CLAMP




(#) 13MHHS
SINGLE PIN
ONLY FOR TC Ø25




(#) 13LAH (AISI 304)
(#) 13LAH-...-316SS (AISI 316)
SINGLE PIN
FROM TC Ø34 AND UP



(#) 13MHHM
DOUBLE PIN
FROM TC Ø34 AND UP



(#) 13MHHS
3 SEGMENTS
FROM TC Ø34 AND UP



(#) 13MHP
HIGH PRESSURE

CODE	ØTC	ASME BPE BS 4825	DIN 32676	ISO 2852	SMS 3008
(#) -A075	25	¼"	DN 6	DN 6	12
		⅜"	DN 8	DN 8	18
		½"	-	DN 10	-
		¾"	-	-	-
(#) -C075	34	-	DN 10	-	-
		-	DN 15	-	-
		-	DN 20	-	-
(#) -A150	50.5	1"	DN 25	DN 15	25
		1"½	DN 32	DN 20	32
		-	DN 40	DN 25	38
(#) -A200	64	2"	DN 50	DN 32	51
		-	-	DN 40	-
(#) -A250	77.5	2" 1/2	-	DN 50	64
(#) -A300	91	3"	DN 65	DN 65	76
(#) -C300	106	-	DN 80	DN 80	-
(#) -A400	119	4"	DN 100	-	102
(#) -H400	130	-	-	DN 100	-
(#) -C500	155	-	DN 125	DN 125	-
(#) -A600	167	6"	-	-	-
(#) -C600	183	-	DN 150	DN 150	-
(#) -A800	217.7	8"	-	-	-
(#) -C800	233.5	-	DN 200	DN 200	-
(#) -AA10	268.5	10"	-	-	-
(#) -AA12	319.3	12"	-	-	-

DATASHEETS

Last updates can be found on our website - www.aerreinox.it
In the interests of development of the product, we reserve the right to change the specifications without prior notice

Aerre Inox S.r.l.
Via Gerola n.4 – 26010 FIESCO (CR) Italy
Tel. +39. 0374.370828 info@aerreinox.it
www.aerreinox.it VAT IT 00962930194

Technical Information:

Material: AISI 304 – 1.4301
Standard with **wing nut** (except for 13MHP)
On request with **hexagon nut**

MAX. SERVICE RATING:

Model *13MHHS* - ASME BPE/BS4825 sizes

Temp/Press.		½" - ¾"
@ 70°F	**psi**	1500
@ 21°C	**bar**	103
@ 250°F	**psi**	1200
@121°C	**bar**	82

Model *13MHHM* - ASME BPE/BS4825 sizes

Temp/Press.		1" - 1"½	2"	2"½	3"	4"	6"	8"	10"	12"
@ 70°F	**psi**	500	450	400	350	200	150	100	100	50
@ 21°C	**bar**	34.5	31	27.5	24	13.8	10	6.5	6.5	3.5
@ 250°F	**psi**	250	250	200	150	125	75	50	30	n.a.
@121°C	**bar**	17	17	13.5	10	8.5	5	3.5	2	n.a.

Wing nut tightening torque = 5 Nm
Service Ratings are based on hydrostatic tests using standard Buna material gaskets, with proper expansion of ferrules, assembly of joints and absence of shock pressure.
For temperature above 121°C it is recommended to use 13MHP clamp.
Please note that these data are not a working condition statement, they shall be intended only as an indication. We suggest to check the service ratings on the specific application.

DATASHEETS

Last updates can be found on our website - www.aerreinox.it
In the interests of development of the product, we reserve the right to change the specifications without prior notice

Aerre Inox S.r.l.
Via Gerola n.4 – 26010 FIESCO (CR) Italy
Tel. +39. 0374.370828 info@aerreinox.it
www.aerreinox.it VAT IT 00962930194